

EVX-5300/5400 SERIES

DIGITAL MOBILE RADIOS
DMR Tier 2 Standard

Vertex Standard

eVerge™

SPECIFICATION SHEET

Evolve to Better Communication and Value

You can afford to enhance your communications with the digital performance of eVerge™ two-way radios. eVerge™ radios are compact and precision-engineered to deliver value without sacrificing quality — giving you more capabilities and the flexibility you need to communicate at your best.

Conversion Made Easy with Analogue Integration

eVerge™ radios operate in both analogue and digital modes and can be used with any existing analogue two-way radios.

Do Digital Right: Stay Compatible and Maximize Efficiency

eVerge™ digital radios operate using the TDMA protocol for spectrum and power efficiency and lower total equipment cost compared to FDMA.

Better Radio Call Quality

Digital eliminates noise and static from voice transmit to only deliver the intended voice message crisply and clearly. eVerge™ digital radios feature the AMBE+2™ vocoder for enhanced voice quality.

Better Message Control and Privacy

Control who you call and who gets your message in digital mode. Digital radios each have a unique ID enabling users to select who they need to call or send a text message without including others.

Better Coverage and Connection Monitoring with ARTS II™

Get ultra-clear audio right up to the edge of the transmit range. And, with Vertex Standard's exclusive Auto-Range Transpond System [ARTS II], you will always know when you are in or out of range with another ARTS II-equipped radio.

Worker Safety Features

As with all Vertex Standard mobile radios, eVerge™ mobile radios include Emergency alert for enhanced driver safety.

Operators can activate the Lone Worker function when leaving equipment or a vehicle temporarily. If a problem arises while away, the radio switches to Emergency mode to alert help.

Option Board Expandable

The EVX-5400 mobiles are designed for future feature expansion and supporting third-party option board development, therefore enabling additional features as location tracking with GPS, telemetry, etc.



EVX-5300



EVX-5400



Back

165 x 45 x 155 mm (W x H x D)



Option Board
Expandability

DMR
DIGITAL MOBILE RADIO ASSOCIATION



Additional Features

- ▶ 6 Programmable keys
- ▶ 8-Character alpha numeric display [EVX-5400]
- ▶ Programmable tri-color LED
- ▶ Voice compander
- ▶ Minimum volume control
- ▶ RSSI Indicator [EVX-5400]
- ▶ Direct channel entry [EVX-5400]
- ▶ CTCSS/DCS encode/decode
- ▶ MDC-1200® encode/decode
- ▶ 2-Tone encode/decode
- ▶ 5-Tone encode/decode
- ▶ Lone worker alert
- ▶ Emergency alert
- ▶ DTMF Speed dial
- ▶ DTMF Paging
- ▶ Remote stun/kill/revive
- ▶ Priority scan
- ▶ Follow-me scan
- ▶ Dual watch
- ▶ Public address/horn alert
- ▶ D-Sub 15-pin accessory connector
- ▶ Radio-to-radio cloning

Digital Mode Features

- ▶ Basic privacy
- ▶ Enhanced privacy [EVX-5400]
- ▶ Text messaging
- ▶ All call, Group call, Individual call
- ▶ Escalart
- ▶ Remote monitor
- ▶ PTT ID encode
- ▶ Mixed mode scan
- ▶ One touch access [EVX-5400]
- ▶ 128 Record contact list [EVX-5400]

Accessories

- ▶ MH-67A8J: Standard microphone
- ▶ MH-75A8J: Keypad microphone [16 keys]
- ▶ MD-12A8J: Desktop microphone
- ▶ MLS-100: External speaker, 12W
- ▶ LF-6: DC Line filter

EVX-5300/5400 Series Specifications

| General Specifications | | |
|--------------------------------|---|--|
| Frequency Range | VHF: 136 – 174 MHz | UHF: 403 – 470 MHz 450 – 520 MHz [Non-CE] |
| Number of Channels and Groups | 8/1 (EVX-5300); 512/32 (EVX-5400) | |
| Power Supply Voltage | DC 13.6V +/- 20% | |
| Channel Spacing | 25/20/12.5 kHz | |
| Current Consumption | TX: 10 A, RX: 2.5A, Standby: 0.4 A [50 W/45 W models] TX: 7 A, RX: 2.5A, Standby: 0.4 A [25 W CE models] | |
| Operating Temperature Range | -30° C to +60° C | |
| Storage Temperature Range | -40° C to + 85° C | |
| Dimension [H x W x D] | 165 x 45 x 155 mm | |
| Weight [Approx.] | 2.2 kg | |
| Receiver Specifications | | |
| Sensitivity: | Analogue 12 dB SINAD: 0.25 uV; 20dB SINAD: 0.4 uV Digital 1% BER: 0.28 uV | |
| Adjacent Channel Selectivity | ETSI EN 300: 60dB @ 12.5KHz ETSI EN 300: 70dB @ 20/25KHz | |
| Intermodulation | 65 dB | |
| Spurious Rejection | 70 dB | |
| Audio Output | Internal: 4 W @ 20 Ohms External: 12 W @ 4 Ohms < 5% THD | |
| Hum and Noise | -40 dB @ 12.5 kHz, -45 dB @ 25 kHz | |
| Conducted Spurious Emission | -57 dBm < 1GHz | |
| Transmitter Specifications | | |
| Output Power | VHF: 25/10/5 W [CE] 50/25/10 W (non-CE) | UHF: 25/10/5 W [CE] 45/25/10 W (non-CE) |
| Emission Designator [Analogue] | 16K0F3E/14K0F3E/11K0F3E | |
| Modulation limiting [Analogue] | +/- 5.0 kHz @ 25 kHz, +/- 4 kHz @ 20 kHz, +/- 2.5 kHz @ 12.5 kHz | |
| Conducted Spurious Emission | -36 dBm <1 GHz, -30 dBm >1 GHz | |
| Hum and Noise | -40 dB @ 12.5 kHz, -45 dB @ 25 kHz | |
| Audio Distortion | 3% | |
| 4FSK Digital Modulation | Data: 7K60F1D/7K60FXD Voice: 7K60F1E/7K60FXE | |
| Digital Protocol | ETSI TS 102 361-1, -2, -3 | |

Applicable MIL-STD

| Standard | Methods/Procedures | | | | |
|-------------------|--------------------|---------------|---------------|--------------------|--------------------|
| | MIL 810C | MIL 810D | MIL 810E | MIL 810F | MIL 810G |
| Low Pressure | - | 500.2/I | 500.3/I | 500.4/I | 500.5/I |
| High Temperature | 501.1/I,II | 501.2/I | 501.3/I | 501.4/I | 501.5/I |
| Low Temperature | 502.1/I | 502.2/I, II | 502.3/I, II | 502.4/I, II | 502.5/I, II |
| Temperature Shock | 503.1/I | 503.2/II | 503.3/I | - | - |
| Solar Radiation | - | - | 505.3/II | 505.4/I | - |
| Rain | 506.1/II | 506.2/II | 506.3/II | 506.4/III | 506.5/I, III |
| Humidity | 507.1/II | 507.2/II | 507.3/II | - | - |
| Salt Fog | - | 509.2/I | 509.3/I | 509.4/I | 509.5/I |
| Dust | - | - | 510.3/I | - | - |
| Vibration | 514.2/VIII, X | 514.3/Cat. 10 | 514.4/Cat. 10 | 514.5/ Cat. 20, 24 | 514.6/ Cat. 20, 24 |
| Shock | 516.2/I, III, V | 516.3/I, IV | 516.4/I, IV | 516.5/I, IV | 516.6/I, IV |