

## 3M™ Peltor™ Ground Mechanic Adapters

FL5008 GB, FL5008-02 GB

### Product description

The PTT button is logically placed so that it is easy to access with either hand. The design makes it easy to use even with heavy gloves. The PTT button has a specific pressure point. The jack is at a 10 degree angle to the fixed cord and positioned so that the headset is easy to plug in and unplug in all situations.

### Key Features:

- Designed to fit the shape of the hand
- Clamp can be twisted 360 degrees
- Oil resistant cable

### Applications

- Ground Mechanic work

### Standards and Approval:

The Product has been shown to meet the requirements of the European Directive 2004/108/EC and is thus CE marked. The product has been verified in accordance with EN61000-6-2:2005.

### Size:

PTT house: 80x60x40 mm

### Materials and data:

Box: TPE

Cable: Self extinguishing PUR sheeting

### Connector and cable:

PTT house connector: 4-pole, TP-120 equivalent

### Use and storage:

Storage temperature: -20°C to +55°C, humidity <85%

Usage temperature: -20°C to +55°C

Maximum recommended shelf life: 5 years

### Use limitations:

Never modify or alter this product.



Model	Cable	Connector
FL5008 GB	6-cores neon green, 6,5 m	3-pole ∅ 6,3 mm
FL5008-02 GB	6-cores neon green, 3,0 m	3-pole ∅ 6,34 mm

