



Peltor™ Tactical™ XP

Electronic Level Dependent Ground Mechanic Headset



MT1H7F2-07-01 GB

- Fail safe functions which enable communication if batteries run out
- Level dependent function that lets you hear ambient sound, conversation, machine sounds and warning signals etc.
- Electronic voice guided menu system
- Equipped the following functions: volume for the level dependent function, balance, adjustable release time, equalizer, volume for external input and external input mode
- Plenty of space for the ear
- Last setting is stored when switched off
- Automatic shut-off after two hours if no function is used
- Warning signal when power is low, before shut-off
- Battery life time approximately 1000 hours

Description

Headset GM

Product code

MT1H7F2-07-01 GB

Attachment

Foldable Head band

Weight (g)

400

Colour



MT1H7F2-07-01 GB

Frequency (Hz)	125	250	500	1000	2000	4000	8000
Mean Attenuation (dB)	13,8	21,5	30,9	36,6	35,9	35,5	39
Standard Deviation (dB)	1,8	0,9	1,3	1,5	5,5	3,1	2,3
Assumed Protection (dB)	12,0	20,6	29,6	35,1	30,4	34,4	36,7

SNR=31dB H=32dB M=25dB L=20dB

Ground Mechanic Adapter

The headset model lets you connect with a separate Peltor™ adapter.

The PTT button is located on the separate adapter.

Product code:

FL5006 GB

Cable

Hi-Viz 3,0 - 6,0 m LAU

Plug

original plug NP3TB-B

FL5006-02 GB

Hi-Viz 3,0 - 6,0 m LAU

NP3C-BAG / Peltor™ Molded

FL5006-03 GB

Hi-Viz 3,5 - 10,0 m LAU

NP3C-BAG / Peltor™ Molded

PTT switch

FL5007 GB

Hi-Viz 1,5 - 6,5 m LAV

original plug NP3TB-B

Kevlar cable

FL5007-02 GB

Hi-Viz 1,5 - 6,5 m LAV

NP3C-BAG / Peltor™ Molded

Kevlar cable

FL5007-04 GB

Hi-Viz 1,8 - 7,5 m LAV

NP3C-BAG / Peltor™ Molded

Kevlar cable

FL5008 GB

Hi-Viz 6,5 m LAU

original plug NP3TB-B

FL5008-02 GB

Hi-Viz 3,0 m LAU

NP3C-BAG / Peltor™ Molded

